BUC310RC30N
BUC315RC30N
BUC320RC30N
BUC320FRC30N
BUC332RC30N
BUC510RC30N
BUC520RC30N
BUC532RC30N
BUC540RC30N
BUC550RC30N

See current catalogue for further detail

IP66 Combination Switched Socket with 30mA RCD protection

Buffalo offers an extensive range of IP66 rated Combination Switched Sockets that are available in three-pin 10A and 15A, and five-pin 10A, 20A, 32A, 40A and 50A designs.

This range has now been expanded to include Wolverine range 30mA RCD protected combinations mounted in BU-4DIN
covers on BUBB4G four gang enclosures and pre-wired for ease of installation for the end user.

Cable links and assembles have been tested in accordance with AS/NZS3100 to ensure suitable thermal performance.

The RCD protected range currently consists of:

- Single phase Flat pin - 10A and 15A combinations
- Size 1 Three Phase 5 pin - 10A and 20A combinations
- Size 2 Three Phase 5 pin - 32A - 50A combinations

As standard the DIN covers are non-power available variants.

Other options may be available upon special request.

Pin & Volt	Cat No.	Current Rating (A)	Pin Config	Pin Config Code (Table 1)	Enclosure	AC21 Rating (A)	AC23A Rating (A)	M Rating	Minimum Conductor Size (mm^2)	Maximum Conductor Size (mm^2)	Dimensions H* x W x D (mm)	Matching Plug Straight	Matching Plug Angled
3 Pin 250V~	BUC310RC30N	10	3 Flat	A	BUBB4G	10	10	200	1.5	6	101x101x111	BUP310	-
	BUC315RC30N	15	3 Flat	B	BUBB4G	15	15	200	1.5	6	101x101x111	BUP315	-
	BUC320RC30N	20	3 Round	G	BUBB4G	20	20	200	2.5	16	101x101x111	BUP320	BUPA320
	BUC320RC30FRN	20	3 Flat	E	BUBB4G	20	20	200	2.5	16	101x101x111	BUP320F	-
	BUC332RC30N	32	3 Round	H	BUBB4G	32	20	200	2.5	16	101x101x111	BUP332	BUPA332
5 Pin 500V~	BUC510RC30N	10	5 Round	N	BUBB4G	10	10	200	2.5	6	101x101x111	BUP510	BUPA510
	BUC520RC30N	20	5 Round	O	BUBB4G	20	20	200	2.5	6	101x101x111	BUP520	BUPA520
	BUC532RC30N	32	5 Round	P	BUBB4G	32	20	200	6	16	101x101x111	BUP532	BUPA532
	BUC540RC30N	40	5 Round	Q	BUBB4G	40	25	200	6	16	101x101x111	BUP540	BUPA540
	BUC550RC30N	50	5 Round	R	BUBB4G	50	25	200	6	16	101x101x111	BUP550	BUPA550

Note: All units are made to order with a 4-week lead time.
Please enquire for availability, and pricing.



Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

GSM Electrical (Australia) Pty Ltd
5-9 Rundle Street, Kent Town SA 5067
P: 1300 301 838 | E: service@gsme.com.au
www.gsme.com.au

100% AUSTRALIAN OWNED & OPERATED

10 Yr Warranty TRADER