


CBGSCC20L CBGSCC25L

See current catalogue for further detail

Straight Glands for Corrugated Conduit

- Colour: Electric Grey
- Material: PVC (Polyvinyl chloride)
- Thread type: M20 & M25
- Thread pitch: 1.5mm
- Device composition: Lock nut
- Installation direction: Straight
- Lower / Upper temperature range: -15°C / 60°C
- Product application: Diameter 20mm & 25mm tube
- Standards: AS/NZS61386.1:2015;
IEC 61386-1: 2008 Part 1: General requirements;
IEC 61386-21: 2002 Part 21: Particular requirements – Rigid conduit systems



Catalogue Number	Size Spec (mm)	D	d	L	H	d1
CBGSCC20L	20	30.0	20.3	20.0	39	18.8
CBGSCC25L	25	37.0	25.4	26.0	49	23.9

Catalogue Number	Description
CBCPPS20	Coupling Plain to Screwed 20mm PVC Grey
CBCPPS25	Coupling Plain to Screwed 25mm PVC Grey

Certification Number:

AS/NZS61386.1; IEC 61386-1; IEC 61386-21; IEC 60670-1

GSM Electrical (Australia) Pty Ltd

5-9 Rundle Street, Kent Town SA 5067

P: 1300 301 838 | E: service@gsme.com.au

www.gsme.com.au

