CBJBR1HD20
CBJBR1HD25
CBJBR2HD20
CBJBR2HD25
CBJBR3HD20
CBJBR3HD25
CBJBR4HD20
CBJBR4HD25

See current catalogue for further detail

Junction Boxes

- Colour: Electric Grey
- Material: PVC (Polyvinyl chloride)
- Lower / Upper temperature range: -15°C / 60°C
- Product application: Diameter 20mm & 25mm tube
- Heavy Duty
- Standards: AS/NZS IEC 60670-1:2015 Boxes and enclosures for electrical accessories for household and similar fixed electrical installations -- Part 1: General requirements.



Catalogue Number	Size Spec (mm)	D	d	L	D1	H1	H2
CBJBR3HD20	20	24.40	20.25	20.00	65.60	41.00	105
CBJBR3HD25	25	29.4	25.25	25	65.6	41	115

Trader Cobra conduit fittings have now been tested and approved for HD applications as per IEC 61386-1: 2008+AMD1: 2017 & IEC 61386-21:2021.

GSM Electrical Trader reserves the right to maintain the MD part codes of previous batches of Trader Cobra Conduit fittings. These products are made and certified to the same standard as their new HD counterparts.





Catalogue Number	Size Spec (mm)	D	d	L	D1	H1	H2
CBJBR4HD20	20	24.4	20.25	20	65.6	41	105
CBJBR4HD25	25	29.4	25.25	25	65.6	41	115

Catalogue Number	Description
CBJBR3HD20	Junction Box Round 3 Way 20mm Shallow Heavy Duty PVC Grey
CBJBR3HD25	Junction Box Round 3 Way 25mm Shallow Heavy Duty PVC Grey
CBJBR4HD20	Junction Box Round 4 Way 20mm Shallow Heavy Duty PVC Grey
CBJBR4HD25	Junction Box Round 4 Way 25mm Shallow Heavy Duty PVC Grey

Certification Number:
AS/NZS IEC 60670-1:2015

GSM Electrical (Australia) Pty Ltd
5-9 Rundle Street, Kent Town SA 5067
P: 1300 301 838 | E: service@gsme.com.au
www.gsme.com.au