

COAC32SO COAC32PL

See current catalogue for further detail

* The Clipsal brand and associated products are Trademarks of Schneider Electric (Australia) Pty Ltd.

GSM Electrical (Australia) Pty Ltd, the TRADER brand and it's products, have no endorsement or affiliation with Schneider Electric Pty Ltd.

Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended.

It is important to ensure that switches are turned off before cleaning.


Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

TV Socket F to Pal Type Connection


COAC32SO

- Rating: 250V a.c. 32A
- Dimensions: 116 x 76 x 43 mm
- Standards: AS/NZS 3131 and AS/NZS 3100
- Approval number: GMA-524664



COAC32PL

- Plug rating: 250V a.c. 32A
- Standards: AS/NZS 3131 and AS/NZS 3100
- Plug approval number: GMA-524663
- Cable rating: 250V/440V, V-90HT, Ordinary duty
- Cable dimensions: 3G 4.0mm², 1.8m length
- Cable standard: AS/NZS 3191
- Cable approval number: SAA251289



Catalogue Number	Description
COAC32PL	Appliance Coupler Plug V 90HT Ordinary Duty 32A 250V ac H05VV F 3G4.0mm ² Lead 1.8m White
COAC32SO	Appliance Coupler Socket Outlet 32A 250V ac White

Certification Number:

COAC32SO: GMA-524664

COAC32PL: GMA-524663

GSM Electrical (Australia) Pty Ltd

5-9 Rundle Street, Kent Town SA 5067

P: 1300 301 838 | E: service@gsme.com.au

www.gsme.com.au

