LEPP2G
LEPP152G
LEPPSW2G

See current catalogue for further detail

Double Power Points

- Power points approved to AS/NZS3112
- Fits standard Australian wall boxes and mounting accessories that use 84mm mounting centres
- Uses brass tunnel terminals that have the screws backed out for easier installation of cabling. Power point terminals have 6mm bore to suit 4 x 2.5mm2 cable. Switch terminals have 4.1mm suit 4 x 1.5mm2
- Combination head screws for the power point terminals
- Uses 'Cat Flap' screw covers for IP rating mounting screws
- Dolly indicator colour green
- Covers, plates and dollies are made from UV stabilised polycarbonate to avoid discolouring to yellow
- Standard colour is white. Black and Brushed Aluminium also stocked - please check availability
- Typical example of size seen below:



Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

Catalogue Number	Description
LEPP2G	Power Point Switched 2 Gang 10A 250V ac White
LEPP152G	Power Point Switched 2 Gang 15A 250V ac White
LEPPSW2G	Power Point Switched 2 Gang 10A 250V ac with Extra Switch 16AX 20A White

*When ordering **BLACK** product add "**BK**" at end of catalogue number, ie LEPP2GBK*

When ordering REPLACEMENT COVERS ONLY add "CO" at end of catalogue number, ie LEPP2GCO

Certification Number:
GMA-500347-EA
GMA-500348-EA

GSM Electrical (Australia) Pty Ltd
5-9 Rundle Street, Kent Town SA 5067
P: 1300 301 838 | E: service@gsme.com.au
www.gsme.com.au