
SNSWDPOV45WW
SNSWDPOV45WWH

See current catalogue for further detail

Oven Switches

- Power points approved to AS/NZS3112.
- Fits standard Australian wall boxes and mounting accessories that use 84mm mounting centres
- Uses brass tunnel terminals that have the screws backed out for easier installation of cabling. Power point terminals have 6mm bore to suit 4 x 2.5mm^2 cable. Switch terminals have 4.1mm suit 4 x 1.5mm2 .
- Combination head screws for the power point terminals.
- Uses 'Cat Flap' screw covers for IP rating mounting screws.
- Dolly indicator colour green.
- Covers, plates and dollies are made from UV stabilised polycarbonate to avoid discolouring to yellow
- Standard colour is white. Available in Black, White/Silver and Black/Silver - Please check availability.
- Typical example of size seen below:



Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic).

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.



Catalogue Number	Description
SNSWDPOV45WW	Switch Oven 45A 250V ac Double Pole White Cover White Grid
SNSWDPOV45WWH	Switch Oven 45A 250V ac Double Pole White Cover White Grid Horizontal

*When ordering **BLACK/BLACK** product replace "**WW**" with "**BB**" at end of catalogue number, ie SNPP2GBB*
*When ordering **BLACK/SILVER** product replace "**WW**" with "**BS**" at end of catalogue number, ie SNPP2GBS*
*When ordering **WHITE/SILVER** product replace "**WW**" with "**WS**" at end of catalogue number, ie SNPP2GWS*

Certification Number:
GMA-514698

GSM Electrical (Australia) Pty Ltd
5-9 Rundle Street, Kent Town SA 5067
P: 1300 301 838 | E: service@gsme.com.au
www.gsme.com.au