

WOLVERINE



Wolverine Switchboards

Outdoor Surface Mounted Switchboard

12, 18 & 24 module wide

- The WOSBWP9, WOSBWP12, WOSBWP18 and WOSBWP24 are designed for outdoor surface mounting use only and intended for use to accommodate circuit protection devices such as circuit breakers; RCDs, isolating switches, surge/over-voltage protection and other such products.
- They are intended for use in domestic or commercial applications.
- They MUST be installed by a licensed electrician and follow AS/NZS3000 wiring rules.
- They comply and have been tested in accordance with AS/NZS61439.3
- IP65 from the front surfaces when mounted to AS 60529.
- Ipk: 17kA for the enclosure assembly.
- Class 2 assembly.
- 100A rated assembly and contains Neutral and Earth bars with double rows of screws.
- Parts pack includes 80A rated bus bar, sticker labelling pack in red and green for non-RCD protected and RCD protected circuit identification, pole fillers (full and half DIN module sizes)



WOSBWP9



WOSBWP12



WOSBWP18



WOSBWP24

INTERFACE CHARACTERISTIC

Voltage ratings

- Rated voltage (Un): 415V
- Rated operational voltage (Ue): 415V
- Rated insulation voltage (Ui): 1000V
- Rated impulse withstand voltage of assembly (Uimp): 4000V
- Complies with minimum overvoltage category III according IEC

60364-4-44

Current ratings

- Rated current of the ASSEMBLY (InA) : 100A
- Rated peak withstand current (Ipk): 17kA
- Rated conditional short-circuit current of an ASSEMBLY (Icc): 10kA

Rated diversity factor (RDF) 1-0.9

Rated frequency (fn) 50Hz

Pollution degree: 2

Fixed stationary installation.

Installation to be carried out by a skilled licensed electrician

Mechanical impact protection: IK05

For protection against electric shock requires screws to be removed to access live parts.

Type B distribution board

The rating of loose busbars. 80A end fed or 100A centre feed.

Neutral link rating : 100A

Overall dimensions:

- 9 module: 219mm(w) x 200mm(h) x 101mm(d)
- 12 module: 273mm(w) x 230mm(h) x 101mm(d),
- 18 module: 381mm(w) x 250mm(h) x 114mm(d),
- 24 module: 273mm(w) x 400mm(h) x 114mm(d)

Weight:

- 9 module: 0.752g,
- 12 module: 1.103g,
- 18 module: 1.825kg,
- 24 module: 2.308kg

